



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	1 / 12

1. IDENTIFICATION

A. Product name : High purity n-Heptane

B. Recommended use : Solvents, coatings, foaming agents, fuels, chemicals for mines, rubber production and processing, etc.
restriction on use : Not available

C. Manufacturer / Supplier / Distributor information :

1) Manufacturer information :

Company name	SceneWay Petroleum Chemical Co.,Ltd.		
A d d r e s s	No.169-1,Fangshui Road,Nanjing chemical industrial , China		
Telephone number	+86-25-5871-5039	F a x n u m b e r	+86-25-5871-5037

2) Supplier/Distributor information :

Company name	SceneWay Petroleum Chemical Co.,Ltd.		
A d d r e s s	No.169-1,Fangshui Road,Nanjing chemical industrial , China		
Telephone number	+86-25-5871-5039	F a x n u m b e r	+86-25-5871-5037

3) Writter information :

D e p a r t m e n t	PSM Team		
Telephone number	+86-25-5871-5039	F a x n u m b e r	+86-25-5871-5037

2. HAZARD IDENTIFICATION

A. GHS Classification:

1) Physical hazards

- Flammable liquids : Category2

2) Health hazards

- Skin corrosion/irritation : Category2

- Serious eye damage/irritation : Category2A

- Specific target organ toxicity(Single exposure) : Category3(Narcotic effects)

- Specific target organ toxicity(Single exposure) : Category3(Respiratory tract irritation)

- Specific target organ toxicity(Repeated exposure) : Category2

- Aspiration hazard : Category1

3) Environmental hazards

- Acute aquatic toxicity : Category1

- Chronic aquatic toxicity : Category1



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	2 / 12

B. GHS label elements

1) Hazard symbols :



2) Signal words : Danger

3) Hazard statements :

H225 Highly flammable liquid and vapor

H304 May be fatal if swallowed and enters airways

H315 Causes skin irritation

H319 Causes serious eye irritation

H335 May cause respiratory irritation.

H336 May cause drowsiness and dizziness.

H373 May cause damage to organs through prolonged or repeated exposure (Refer Section SDS 11)

H400 Very toxic to aquatic life

H410 Very toxic to aquatic life with long lasting effects

4) Precautionary statements :

■ Prevention

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+P352 IF ON SKIN: Wash with plenty of soap and water

P233 Keep container tightly closed.

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P243 Take precautionary measures against static discharge.

P260 Do not breathe gas/mist/vapors/spray.

P261 Avoid breathing gas/mist/vapors/spray.

P264 Wash hands thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P273 Avoid release to the environment.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

■ Response

P301+P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	3 / 12

breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P314 Get medical advice/attention if you feel unwell.

P321 Specific treatment.

P331 Do NOT induce vomiting.

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P362 Take off contaminated clothing and wash before reuse.

P370+P378 In case of fire: Use Suitable extinguishing media for extinction(Refer Section SDS 5).

P391 Collect spillage.

■ Storage

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

■ Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulation

C. Other hazards which do not result in classification : (NFPA Classification)

NFPA grade (0 ~ 4 level) : Health : 2 , Flammability : 3, Reactivity : 0

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	Trade names and Synonyms	CAS No.	Content(%)
n-Heptane	Heptane	142-82-5	99.5-100

4. FIRST AID MEASURES

A. Eye contact :

- Do not rub your eyes.
- Immediately flush eyes with plenty of water for at least 15minutes and call a doctor/physician.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Remove contact lenses if worn.



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	4 / 12

B. Skin contact :

- Flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
- Laundering enough contaminated clothing before reuse.
- Get medical attention immediately.
- Go to the hospital immediately if symptoms(flare, irritate) occur.
- Wash thoroughly after handling.

C. Inhalation contact :

- When exposed to large amounts of steam and mist, move to fresh air.
- Take specific treatment if needed.
- Get medical attention immediately.

D. Ingestion contact :

- About whether I should induce vomiting Take the advice of a doctor.
- Rinse your mouth with water immediately.
- Get medical attention immediately.
- If swallowed, large amounts of water to drink and do not induce vomiting.

E. Delayed and immediate effects and also chronic effects from short and long term exposure:

- Not available

F. Notes to physician

- Notify medical personnel of contaminated situations and have them take appropriate protective measures.

5. FIREFIGHTING MEASURES

A. Suitable (Unsuitable) extinguishing media :

- 1) Suitable extinguishing media : alcohol form, carbon dioxide, water spray, dry sand and earth
- 2) Unsuitable extinguishing media: Avoid use of water jet for extinguishing.
- 3) In case of large fire : spraying, watering

B. Specific hazards arising from the chemical

- Highly flammable liquid and vapor
- Polymerization may cause fire and explosion.
- Vapor may be released to the ignition source and ignited.
- May form explosive mixture at or above flash point
- Container may explode on heating



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	5 / 12

- Highly flammable: easily ignited by heat, spark, flame
- Leaks are a fire / explosion hazard.
- Vapors may explode indoors, outdoors, and in drains
- Vapor may travel to the source of ignition and flash back.
- Vapors may cause dizziness or suffocation without knowledge.
- May cause irritating, corrosive and toxic gases in case of fire
- Inhalation and contact may irritate or burn the skin and eyes.

C. Special protective actions for firefighters :

- In the event of a leaking fire, do not extinguish the fire unless you can safely prevent the leaking.
- Remove all ignition sources if safe to do so.
- Fire fighters should wear appropriate protective equipment.
- Please digested outside the area by keeping a safe distance.
- Find and use appropriate evolutionary methods for your surroundings.
- Wear appropriate protective equipment if necessary.
- Move container from fire area if it is not hazardous.
- Vapors or gases may ignite at distant ignition sources and spread rapidly..
- Do not pour water directly into the exposure source or safety equipment as it may freeze in the event of a tank fire.
- In case of tank fire, extinguish at maximum distance or use unmanned fire fighting equipment.
- Cool containers with large amounts of water even after tank fire has extinguished.
- In the event of a fire in the tank, if there is a high sound level on the pressure relief device or if the tank is discolored, immediately withdraw it.
- In case of tank fire, back off the flame tank.
- In the event of a large fire, use unmanned fire fighting equipment and allow it to retreat if it is impossible.

6. ACCIDENTAL RELEASE MEASURES

A. Personal precautions, protective equipment and emergency procedures :

- Avoid breathing dust / fume / gas / mist / vapors / spray.
- Remove all ignition sources because very fine particles may cause fire or explosion.
- Wipe off any spills immediately and follow all protective precautions.
- Isolate contaminated areas.
- If you do not need to enter or do not have protective equipment, do not go in.
- If possible, turn the leak container to release it as a gas rather than a liquid.
- Do not pour into leak sources directly.
- Use water spray to reduce vapors or scatter vapor clouds and prevent water from coming into



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	6 / 12

contact with spills.

- Always ground all equipment when handling materials.
- Keep the substance scattered.
- Stop the leak if it is not dangerous.
- Some leave flammable residues after evaporation.
- Do not touch a damaged container or spill without adequate protection.

B. Environmental precautions :

- Prevent runoff and contact with waterways, drains or sewers.
- Do not allow vapors to escape through drains, ventilation, or enclosed spaces.
- If large amounts have been spilled, inform the relevant authorities.

C. Methods and materials for containment and cleaning up :

- Pile up the embankment and collect the water for digestion.
- Absorb spillage with inert materials (eg dry sand or earth) and place in a chemical waste container.
- Absorb liquid and rinse contaminated area with detergent and water.
- Notification to central government, local government. When emissions at least of the standard Amount

7. HANDLING AND STORAGE

A. Precautions for safe handling :

- Do not handle until all safety precautions have been read and understood.
- Handle it outdoors or in a well-ventilated area.
- Do not expose, cut, expose, weld, solder, bond, punch, grind or expose to heat, flames, sparks, static electricity or other sources of ignition
- Follow all SDS / warning label precautions, as product residues may remain even after emptying containers.
- Carefully open the cap before opening.
- Be sure to ground all equipment when handling material.

B. Conditions for safe storage, including any incompatibilities :

- Keep away from heat / sparks / open flames / hot surfaces. – no smoking
- Keep container tightly closed in a well-ventilated place.
- Avoid direct sunlight.
- The empty drum should be completely drained, properly blocked and immediately returned to the drum regulator or placed properly.
- The container may be pressurized if exposed to heat.



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	7 / 12

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

A. Exposure limits:

< n-Heptane>

- 1) ACGIH TLV : TWA, 400 ppm (1640 mg/m³) STEL, 500 ppm (2050 mg/m³)
- 2) OSHA PEL : 500ppm 2000mg/m³

B. Engineering controls :

- A system of local and/or general exhaust is recommended to keep employee exposures above the Exposure Limits. Local exhaust ventilation is generally preferred because it can control the emissions of the contaminant at its source, preventing dispersion of it into the general work area. The use of local exhaust ventilation is recommended to control emissions near the source.

C. Individual protection measures, such as personal protective equipment :

1) Respiratory protection :

- Under conditions of frequent use or heavy exposure, Respiratory protection may be needed.
- Respiratory protection is ranked in order from minimum to maximum..
- Consider warning properties before use
- Any chemical cartridge respirator with organic vapor cartridge(s).
- Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
- Any air-purifying respirator with a full facepiece and an organic vapor canister.
- For Unknown Concentration or Immediately Dangerous to Life or Health : Any supplied-air respirator with full face piece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply. Any self-contained breathing apparatus with a full facepiece.

2) Eye protection

- Wear primary eye protection such as splash resistant safety goggles with a secondary protection face shield.
- Provide an emergency eye wash station and quick drench shower in the immediate work area.

3) Hand protection

- Wear appropriate chemical resistant glove.

4) Skin protection

- Wear appropriate chemical resistant protective clothing.

5) Others : Not available

9. PHYSICAL AND CHEMICAL PROPERTIES

A. Appearance : Colorless liquid



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	8 / 12

- B. Odor: Gasoline odor
C. Odor threshold : Not available
D. pH : Not available
E. Melting point/Freezing point : -91 °C / Not available
F. Initial Boiling Point/Boiling Ranges : 98 °C
G. Flash point: -4 °C
H. Evaporation rate : Not available
I. Flammability(solid, gas) : Not applicable
J. Lower/Upper Flammability or explosive limits: 1.1 / 6.7%
K. Vapor pressure: 4.6 kPa (20 °C)
L. Solubility : 0.00034 g / 100 ml (25 ° C, soluble: carbon tetrachloride, ethanol, ether, chloroform, acetone)
M. Vapor density(Air=1) : 3.46
N. Specific gravity(Relative density) : 0.68
O. Partition coefficient of n-octanol/water : 4.66
P. Autoignition temperature : 285 °C
Q. Decomposition temperature: Not available
R. Viscosity : 0.4169 cP (20 °C)
S. Molecular weight : 100.21

10. STABILITY AND REACTIVITY

- A. Chemical Stability :
– This material is stable under recommended storage and handling conditions.
- B. Possibility of hazardous reactions :
– Cylinders exposed to fire may vent and release flammable gas.
- C. Conditions to avoid :
– Avoid contact with incompatible materials and condition.
– Avoid contact with heat, sparks, flame or other ignition sources.
- D. Incompatible materials : Not available
- E. Hazardous decomposition products :
– May cause irritating, corrosive and toxic gases.

11. TOXICOLOGICAL INFORMATION



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	9 / 12

A. Information on the likely routes of exposure

- Respiratory tracts :
 - May be fatal if swallowed and enters airways
 - May cause respiratory irritation.
- Oral : Not available
- Eye-Skin :
 - Causes serious eye irritation
 - Causes skin irritation

B. Delayed and immediate effects and also chronic effects from short and long term exposure

1) Acute toxicity :

- Oral : Not classified
 - LD50 > 5000 mg/kg Rat (ECHA)
- Dermal : Not classified
 - LD50 > 2000 mg/kg Rabbit (ECHA)
- Inhalation : Not classified
 - LC50 = 25,184 ppm/4h Rat (NITE(2009))
 - LC50 = 53 mg/L 4hr (75 mg / L 2 hr conversion value) (HSDB)

2) Skin corrosion/irritation : Category2

- Causes skin irritation in human. (NITE(2006))

3) Serious eye damage/irritation : Category2A

- Causes serious eye irritation. (NITE, ICSC)

4) Respiratory sensitization : Not available

5) Skin sensitization: Not classified

- Non-sensitizing in guinea pigs (ECHA)

6) Carcinogenicity : Not available

- NTP : Not available
- IARC : Not available
- ACGIH : Not available
- EU CLP : Not available

7) Germ cell mutagenicity : Not available

8) Reproductive toxicity : Not classified

- In the inhalation exposure test in rats, negative (ECHA)

9) STOT-single exposure : Category3(Narcotic effects)(Respiratory tract irritation)

- Inhalation exposure studies in rat or mouse resulted in narcotic effects and respiratory irritation. Causes central nervous system depression or mucosal irritation in humans. (NITE(2006))



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	10 / 12

10) STOT-repeated exposure : Category2

– May cause damage to liver through prolonged or repeated exposure. (NITE(2006))

11) Aspiration hazard : Category1

– May be fatal if swallowed and enters airways. (NITE(2006))

12. ECOLOGICAL INFORMATION

A. Ecotoxicity :

- Acute aquatic toxicity : Category1
- Chronic aquatic toxicity : Category1
 - 1) Fish : LC50 = 375 mg/l 96 hr *Oreochromis mossambicus* (ECOTOX)
 - 2) Crustaceans : EC50 = 0.64 mg/L 48hr (ECHA)
 - 3) Algae : Not available

B. Persistence and degradability:

- 1) Persistence :
 - log Kow 4.66 (ICSC)
- 2) Degradability : Not available

C. Bioaccumulative potential :

- 1) Bioaccumulative potential :
 - BCF = 552 (ECHA)
- 2) Biodegradation : Not available

D. Mobility in soil : Not available

E. Other adverse effects : Not available

13. DISPOSAL CONSIDERATIONS

A. Disposal methods

- Since more than two kinds of designated waste is mixed, it is difficult to treat separately, then can be reduction or stabilization by incineration or similar process.
- If water separation is possible, pre-process with Water separation process.
- Dispose by incineration.

B. Special precautions for disposal

- The user of this product must disposal by oneself or entrust to waste disposer or person who other's waste recycle and dispose, person who establish and operate waste disposal facilities.



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	11 / 12

– Dispose of waste in accordance with all applicable laws and regulations.

14. TRANSPORT INFORMATION

A. UN No. (IMDG) : 1206

B. Proper shipping name : HEPTANES

C. Hazard Class : 3

D. IMDG Packing group: II

E. Marine pollutant : Applicable

F. Special precautions for user related to transport or transportation measures

- 1) EmS FIRE SCHEDULE : F-E (Non-water-reactive flammable liquids)
- 2) EmS SPILLAGE SCHEDULE : S-D (Flammable liquids)

15. REGULATORY INFORMATION

A. National and/or international regulatory information :

1) POPs Management Law : Not applicable

2) Information of EU Classification

- Classification
 - [n-Heptane] : F; R11Xn; R65Xi; R38R67N; R50-53
- Risk Phrases
 - [n-Heptane] : R11, R38, R65, R67, R50/53
- Safety Phrase
 - [n-Heptane] : S2, S9, S16, S29, S33, S60, S61, S62

3) U.S. Federal regulations

- OSHA PROCESS SAFETY (29CFR1910.119)
- CERCLA Section 103 (40CFR302.4) : Not applicable
- EPCRA Section 302 (40CFR355.30) : Not applicable
- EPCRA Section 304 (40CFR355.40) : Not applicable
- EPCRA Section 313 (40CFR372.65) : Not applicable

4) Rotterdam Convention listed ingredients : Not applicable

5) Stockholm Convention listed ingredients : Not applicable

6) Montreal Protocol listed ingredients : Not applicable



SAFETY DATA SHEET(SDS)

High purity n-Heptane

Date of issue	2017.02.08
Revision date	Not applicable
Revision number	Not applicable
Page	12 / 12

16. OTHER INFORMATION

A. Reference:

- ☐ EU Regulation 1272/2008
- ☐ TOMES; LOLI ; <http://csi.micromedex.com/fraMain.asp?Mnu=0>
- ☐ UN Recommendations on the transport of dangerous goods 17th
- ☐ IARC Monographs on the Evaluation of Carcinogenic Risks to Humans;
<http://monographs.iarc.fr>
- ☐ ECHA CHEM; <http://echa.europa.eu/web/guest/information-on-chemicals/registered-substances>
- ☐ OECD SIDS; <http://webnet.oecd.org/Hpv/UI/Search.aspx>
- ☐ HSDB; <http://toxnet.nlm.nih.gov/cgi-bin/sis/search2>

B. Key acronyms

- ☐ ACGIH(American Conference of Governmental Industrial Hygienists)
- ☐ ECHA(European Chemicals Agency)
- ☐ OECD(Organization for Economic Co-operation and Development)
- ☐ CERCLA(Comprehensive Environmental Response, Compensation, and Liability Act)
- ☐ IARC(International Agency for Research on Cancer)
- ☐ OSHA(Occupational Safety and Health Administration)
- ☐ NTP(National Toxicology Program)
- ☐ NFPA(National Fire Protection Association)
- ☐ LC₅₀(Lethal Concentration 50% kill)
- ☐ LD₅₀(Lethal Dose 50% kill)
- ☐ EC₅₀(50% Effect Concentration)
- ☐ STEL(Short Term Exposure Limit)
- ☐ TWA(Time weight Average)
- ☐ TLV(Threshold Limit Value)

C. Issue date : 2017-02-08

D. Revision number and Last date revised : Not applicable

E. Other :

- ☐ This SDS is prepared according to the Globally Harmonized System (GHS).